



**SAFETY
JOGGER**
PROFESSIONAL



#####

COOL O2

#####

#####

ESD

####

#####

#####

#####

#####

SJ foam

#####

#####

#####

O2 / SR, ESD, FO, HRO

#####

EU 35-48 / UK 3.0-13.0 / US 3.0-13.5

JPN 21.5-31.5 / KOR 230-315

###

0.436 kg

#####

ASTM F2892:2018


EN ISO 20347:2022+A1:2024



WHT



BLK



Oxygrip / SJ Grip

#####

Oxytraction®

#####

#####

SRC

(SRA + SRB).



#####

#####

#####

#####

#####

#####



(ESD)

ESD #####

#####

#####

#####

#####

100 ## 100 #####.



SRA

#####

#####

#####

#####

#####

#####

SRC

#####

SRA, ## # SRB, ## #

#

#####




#####

#####

#####

#####

#####



#####

#####

#####

#####

#####

#####

**SAFETY
JOGGER**
WORKS

**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

**ENGINEERED
IN EUROPE**

www.safetyjogger.com

#####:
#####, #####, ##### ##### # #####, #####, #####, #####, #####

#####, #####

#####. ## ##### # #
#.

	#####	#####	#####	EN ISO 20347
###	#####			
	###: #####	##/##/##	1.38	# 0.8
	###: #####	##/## ²	17	# 15
#####	#####			
	#####: #####	##/## ² /##	37.3	# 2
	#####: #####	##/## ²	299	# 20
#####	##### SJ foam			
	#####: ##### # ##### (#####/#####) (#####)	#####	25600/12800	25600/12800
#####	#####			
	##### (#####)	## ³	67	# 150
	##### - Ceramic + NaLS - #####	#####	0.35	# 0.31
	#####			
	##### - Ceramic + NaLS - #####-	#####	0.38	# 0.36
	#####			
	SR ##### - ##### + ##### - #####	#####	0.25	# 0.19
	#####			
	##### SR - ##### + ##### - #####	#####	0.33	# 0.22
	#####			
	#####	#####	16.5	0.1 - 1000
	##### (ESD)	#####	20	0.1 - 100
	#####	J	22	# 20

#####.

#####, ##### ##### #####. ## ##### # ##### Safety Jogger, #####
#####.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com